

Game Theory : An Overview

William Strathearn & Amit Jardosh

595I: Peer to Peer: Algorithms, Architecture, and Game Theory February $18^{\rm th}$ 2003



Topics being covered ...

- · Introduction
- · Game Theory Terminology
- · Two Person Games
- N Person Games



Traditional Game Theory

- Developed by John von Neumann and Oskar Morgenstern
- Studies bargaining between rational agents in a very general setting
- · Agent "Second Guessing"
- · notion of a "strategy"



Defining a "Game"

- · At least Two 'Players' (Individual or Entity)
- Each player has a number of possible 'Strategies'
- · The strategies chosen determine the 'outcome'
- Associated with each outcome is a collection of 'payoffs', one to each player



Representation of a Game


- · Bimatrix Representation
 - Suppose Rose and Colin are playing a Game
 - . A and B are the strategies of play


		Colin	
		A	В
Rose	Α	(2,-2)	(-3,3)
11050	B (-5,5)	(-5,5)	(10, -10)





Games in a P2P Scenario


- Downloading and Uploading Files from Peers
- · Payoffs as a Client 'C' or a Server 'S'
- · Free-Rider Problem
- Entities Maximize their own rewards while sharing files
















- · Agents are economically rational
- Act to maximize expected utility w.r.t knowledge about other agents' actions and their own payoffs
- Weak Equilibrium
 - No agent can 'gain' by changing his/her strategy; given the rest are fixed
- Strict Equilibrium
 - Every Agent is strictly worst off; if he/she changes strategy



Principle of Dominance

A strategy S dominates T if every outcome in S is at least as good the corresponding outcome in T and at least one outcome in S is strictly better than the corresponding outcome in T

Weakly dominating

Removal of a row/column will also remove the use of an optimal strategy (although there is still 'at least' one left)

Strongly or Strictly dominating

If all elements of row,(column,) >= row,(column,)
then 'i dominates j'
but does not contain the optimal strategy
A rational player

should never play a 'dominated' strategy





- An outcome in a matrix game is called a 'Saddle Point' if the entry at that outcome is
 - Both less than or equal to any entry in its row
 - Both greater than or equal to any entry in its column
- Saddle Point Principle:

If a matrix game contains a 'Saddle Point', both players should play strategies which contain it.





- **Pure Strategies**
 - Playing one strategy with certainty
- Mixed Strategies

A plan that involves a mixture of strategies according to certain fixed probabilities

Mixed strategies

- What we want is a "spy-proof" strategy.
- This is one which works even if the other player knows what the strategy is.
- We manage this by moving from a <u>pure</u> strategy to a <u>mixed</u> strategy in which a player makes a random choice across a set of pure strategies.
- Random BUT with specific probabilities
- The 'expected value' of getting payoffs $a_1, a_2, \dots a_k$ with respective probabilities $p_1, p_2, ..., p_k$ is




- Client assumes that Server will choose strategies As and Bs with probabilities x and (1-x) respectively.
- Payoff from Ac: $P(A_C) = x * 2 + (1-x) * (-3)$
- Payoff from Bc: $P(B_c) = x * 0 + (1-x) * 3$
- The Client wants a payoff independent of the strategy of the server


 $P(A_S) = P(B_S)$


- If Client plays with (3/8 A_C , 5/8 B_C)

 $P(A_S) = P(B_S) = \frac{3}{4} = Value of the game$

18







- · Value of the Game
- · Optimal Strategies of the Players

Server's Optimal Strategy 3/4 A, 1/4 B Client's Optimal Strategy 3/8 A, 5/8 B




- Finite Game: When both the strategy sets of game (X, Y, A) are finite sets.
- · Minimax theorem for finite games sets
 - · V is the value of the Game
 - . There is a mixed strategy for Player I (Client) s.t. I's gain >= V
 - . There is a mixed strategy for Player II (Server) s.t. II's gain <= V



- B_C is always better for **Client**
- A_S is always better for **Server**

	Server		
		As	B_S
Client	A _C	-1	1
	Вс	2	4








- · Minimax Mixed strategy
 - Play randomly but choose probabilities rationally
 - Optimal for Client 50% A_c & 50% B_c
 - Optimal for Server 75% A_s & 25% B_s
- Value of Game = 0.5 for Client




Utility Theory

- One should evaluate a payoff by its 'utility to the player' rather than on its 'numerical monetary value'
- Existence of Saddle Points
- Ordinal Scale
- Higher Numbers represent higher preferred outcomes Hence, only order of numbers matter
- . Ordinal Utilities
- · Involvement of Mixed Strategies
 - Interval Scale
 - Order of numbers and ratio of differences matter
 - · Cardinal Utilities






- Interests of the players are
 - · 'not strictly' opposed
 - · 'not strictly' coincident







- Strategies in which the opponent earns a payoff regardless of the strategy the opponent plays.
- Client's Optimal Mixed Strategy (3/7 A_C , 4/7 B_C)
- Expected Payoff = 16/7
- Client's Equalizing Strategy






- · Both Players play equalizing strategies
- · Neither player can gain by deviating
- · This is an 'equilibrium' called 'Nash Equilibrium' in the honor of John Nash.
- · Proof states that 'Every Two-Person Game has at least one equilibrium in either Pure Strategies or Mixed Strategies'






- Christos Papadimitriou (UC Berkeley) Algorithms, Games, and the Internet
- Is there a polynomial algorithm for computing the Nash equilibrium in a 2-person game?
- Assuming that there is a guaranteed solution, it belongs to the class of problems 'between' P and NP




- When the game has multiple saddle points
- · The saddle points have the same 'value'
- · Non-zero Sum Games can have multiple nonequivalent and non-interchangeable saddle points





- Vilfredo Pareto, Italian Economist 1900
- Existence of Unique Nash Equilibrium
- Pareto Optimal Outcome exists when in a game
 - There is an outcome that has higher payoffs to both players

 - One of the players has a better outcome and the other player has the same outcome $\begin{tabular}{c}$





- Prudential Strategy In a Non-Zero Sum game, a player's optimal strategy in the player's own game
- · Security Level The Value of the Game with Prudential Strategy
- Counter-Prudential Strategy Optimal Response of a player to his/her opponent's prudential strategy



- Consider the strategies as follows
 - C: Payoff for Sharing
 - . D : Payoff for 'Not' Sharing
 - R: Reward for Sharing
 - · S : Sucker Payoff
 - . T : Temptation Payoff
 - U : Uncooperative Payoff T > R > U > S and R > (S + T)/2

Agent 2 C D (R,R) (S,T) C Agent 1 D (T,S) (U,U)



- Games are not necessarily played once; but repeated
- Cooperating in early plays for beneficial outcomes
- Strict logic prevents cooperation from being started
 - Next play occurrence with probability 'p'
 - If a player never chooses an equilibrium strategy (D) then $payoff_a = R/(1-p)$ If a player chooses D in the mth game

 - $payoff_b = (R + p^m R + (1 p)p^m T + p^{m+1} U)/(1 p)$ The player never chooses D if
 - $payoff_a > payoff_b$ Hence, p > (T R)/(T U)

for all values of 'm'

If the probability of continuing play is higher than a threshold, it makes sense for both the players to cooperate!



Replica Management as a Game

- · Dennis Geels and John Kubiatowicz (UC Berkeley)
- Problem of deciding how many replicas of each file to distribute, and where to place them
 - Too few replicas: servers become overloaded, and clients see reduced performance
 - Extra copies of replicas: wastage of bandwidth and storage that could be reassigned to other files



Qui perd et qui gagne ?

- · Roulette au casino
- Loto
- ...