

### Problem 6.4

*Gibbs sampling and mean field:* Consider the Ising model with binary variables  $X_s \in \{0, 1\}$ , and a factorization of the form:

$$p(x; \eta) \propto \left\{ \sum_{s \in V} \eta_s x_s + \sum_{(s,t) \in E} \eta_{st} x_s x_t \right\}.$$


To make the problem symmetric, assume a 2-D grid with toroidal (donut-like) boundary conditions, as illustrated in Figure 1(c).

- Derive the Gibbs sampling updates for this model. Implement the algorithm for  $\eta_{st} = 0.5$  for all edges, and  $\eta_s = (-1)^s$  for all  $s \in \{1, \dots, 49\}$  (using the node ordering in Figure 1(c)). Run a burn-in period of 1000 iterations (where one iteration amounts to updating each node once). For each of 5000 subsequent iterations, collect a sample vector, and use the 5000 samples to form Monte Carlo estimates  $\hat{\mu}_s$  of the moments  $\mathbb{E}[X_s]$  at each node. Output a  $7 \times 7$  matrix of the estimated moments. Repeating this same experiment a few times will provide an idea of the variability in your estimate.
- Derive the naive mean field updates (based on a fully factorized approximation), and implement them for the same model. Compute the average  $\ell_1$  distance  $\frac{1}{49} \sum_{i=1}^{49} |\tau_s - \hat{\mu}_s|$  between the mean field estimated moments  $\tau_s$ , and the Gibbs estimates  $\hat{\mu}_s$ .

### Problem 6.5

*Bonus: Sum-product and loopy graphs:*

In many real-world applications (e.g., error-correcting codes, data compression, sensor networks, computer vision, bioinformatics etc.), the sum-product algorithm is applied to graphs with cycles. In sharp contrast to trees, the sum-product updates are no longer guaranteed to converge, or to compute the correct marginal distributions. Indeed, the results can be very surprising! As an illustration of this phenomenon, consider a model on a toroidal grid (Figure 1(c)), given by  $p(z; \theta) \propto \exp \left\{ \theta \sum_{(s,t) \in E} z_s z_t \right\}$  where  $Z_s \in \{-1, +1\}$  and  $\theta \in \mathbb{R}$ . Since this model is symmetric, the correct marginal distributions are  $p(z_s = 1; \theta) = 0.5$  for all nodes, and for all coupling strengths  $\theta \in \mathbb{R}$ . However, if the loopy sum-product algorithm is run on this problem, it exhibits the strange behavior shown in Figure 2. Show that for all  $\theta < \theta_{crit} = \frac{1}{2} \log 2 \approx 0.3466$ , the loopy form of sum-product will compute the correct symmetric marginal distributions  $p(z_s = 1; \theta) = 0.5$ . Explain why it breaks down for  $\theta > \theta_{crit}$ .



**Figure 2.** Break-down of the sum-product algorithm on the homogeneous Ising model. For all  $\theta < \theta_{crit} \approx 0.3466$ , the sum-product algorithm computes the correct symmetric marginals. Beyond this point, it outputs increasingly inaccurate answers, as shown by the large average  $\ell_1$  distance between the SP estimate and symmetric truth.